

Technical data sheet

Water treatment system with WaterCube nanofiltration module

Description

The WaterCube water treatment system uses a specially coated ceramic membrane to achieve high purification performance in a wide range of applications:

- Industrial wastewater
- Production of process water
- Treatment of surface- and seepage water
- Pre-cleaning to relieve downstream water treatment systems

The advantages of the technology include

- Low operating costs
- Backwashability of the membranes
- Long service life and durability
- High pH and temperature resistance

Membrane specifications

Material	Ceramic compound polymer
Coating material	x
MWCO	x
Min. MgSO ₄ Membrane charge	negative
Inner diameter of the membrane	x

Typical system parameters

Max. Pressure	6 bar
Max. Backwash pressure	4 bar
Operating pressure	4 bar
Energy consumption electr.	approx. 25-30 kWh/m ³ permeate
Temperature Feed	1 - 55 °C
pH range	5 - 9
Chlorine concentration	stable depending on composition
Backwash time	2 - 10 % of operating time

Feed water requirements

Max. TSS	x ppm
Max. particle size	50 µm

Module specifications

Membrane surface size	m ²
-----------------------	----------------

Dimensions of the water treatment system (e.g. 2.5m³/d permeate)

Height	1,8 m
Length	2 m
Width	0,9 m
Weight	250 kg

Construction

Frame construction	Aluminum
Pipework	PE

Dimensions

Water quantity feed	1 – 20.000 m ³ /a (modular)
---------------------	--

Thanks to the modular design of our systems and the adaptability of the coatings, we can respond directly to your application. We can also expand or relieve your existing system. For a personal consultation, please contact

Mrs. Martina Findling
Phone: +49 (0) 162 331 26 21
E-Mail: info@inflatoc.com
gladly at your side!

Mr. Patrick Egeward
Phone: +49 (0) 173 608 04 90
E-Mail: info@inflatoc.com